

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61F 2/32 // A61F 2/36	A1	(11) International Publication Number: WO 93/16663 (43) International Publication Date: 2 September 1993 (02.09.93)
(21) International Application Number: PCT/SE93/00169 (22) International Filing Date: 26 February 1993 (26.02.93) (30) Priority data: 9200597-4 28 February 1992 (28.02.92) SE (71) Applicant (for all designated States except US): AKTIEBO- LAGET ASTRA [SE/SE]; S-151 85 Södertälje (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): ALBREKTSSON, Björn [SE/SE]; Sveagatan 11, S-413 14 Göteborg (SE). CARLSSON, Lars [SE/SE]; S:a Bergavägen 8, S-430 41 Kullavik (SE). JACOBSSON, Magnus [SE/SE]; Orang- erigatan 11, S-412 66 Göteborg (SE). RÖSTLUND, Tord [SE/SE]; Fasanstigen 22, S-430 41 Kullavik (SE). WENNBERG, Stig [SE/SE]; Pl 6266, S-424 57 Angered (SE).	(74) Agents: KALLING, Sven et al.; AB Astra, Patent Depart- ment, S-151 42 Södertälje (SE). (81) Designated States: AT, AU, BB, BG, BR, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI pa- tent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG). Published With international search report.	
(54) Title: HIP JOINT PROSTHESIS <div data-bbox="386 1121 1435 1738"> </div> (57) Abstract <p>The invention relates to a hip joint prosthesis comprising an attachment part for a ball unit (18) being designed to be anchored in the neck of a human femur (collum femoris), said attachment part, which is intended to be inserted into a channel (5, 14) extending through the femoral collum, being provided with parts for carrying a ball or caput (18) intended to be attached to the collum after removal of the head of the collum. The attachment part also comprises a fixture part comprising two main parts, a first part (1) which is to extend through a bore-hole (5) from the collum femoris towards the outer side of the femur and a second part (2) intended to fit into a cylindrical cavity cut into the cancellous bone of the collum.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LJ	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

Hip joint prosthesisTechnical field of the invention.

5 The invention relates to a hip joint prosthesis for
permanent anchoring in the human hip joint comprising an
attachment part for a ball unit designed to be anchored
in the neck of a human femur (collum femoris), said
attachment part, which is intended to be inserted into a
10 channel extending through the femoral collum, being
provided with parts for carrying a ball or caput intended
to be attached to the collum after removal of the head
of the femur.

15 Background of the invention.

20 The present invention is a development of a hip joint
prosthesis of the kind disclosed in WO 89/11837. This
document inter alia discloses a hip joint prosthesis
comprising a primary fixture in the shape of a sleeve,
said sleeve being intended to be inserted into a central
hole bored longitudinally through the collum femoris from
the outer side of the femur and a secondary fixture in
the shape of a cap having a spherical shape intended to
25 be attached to and cover the end of the collum femoris
when the head of the collum has been removed partly or
entirely and the outside of remaining end has been cut to
a cylindrical shape. The primary and the secondary
fixtures are interconnected by means of a bolt which at
30 one end has an internal thread. The bolt is to be
inserted into the sleeve and its internal thread is to be
made to engage a central, threaded stud projecting from
the spherical cap. When the bolt is tightened, the cap is
pressed over the cylindrically cut caput or end of the
35 collum.

The prior art device thus is relatively complicated, both
in construction and use.

5 In some applications it may furthermore not be suitable to use this prior art device. One reason for this is that the shape of the collum may make it difficult to retain enough cortical bone to give the secondary fixture or cap a firm support, since the shape of the collum may vary to a great extent.

10 This prior art device is also designed to be inserted in a two-seance procedure, i. e. some parts of the prosthesis are to be inserted in a first operation, the remaining parts being inserted later in a second operation after a healing period of a few months.

15 Other similar prior art is disclosed for instance in DE-A1-28 45 231, DE-A1-27 24 040, US-A-4,795,473 and US-A-4,005,495.

20 The object of the invention is to achieve a hip joint prosthesis which is simple in construction and use and which is particularly suited for insertion in a one-seance operation and which can be adapted to fit different condtions.

25 Brief description of the inventive concept

30 According to the invention the attachment part in a hip joint prosthesis of the kind described above also comprises a fixture part comprising two main parts, a first part which is to extend through a bore-hole from the collum femoris towards the outer side of the femur and a second part intended to fit into a cylindrical cavity cut into the cancellous bone of the collum.

35 The fixture can be made in one piece but, in one preferred embodiment, comprises two separate parts which are firmly attached to each other before the fitting of the fixture into the femur.

This will result in that the cortical bone will remain intact to a larger degree and that the load conditions will be such that a physiologically appropriate load on the upper part of the collum can be achieved. Forces can be transferred from the fixture to the femur without any noticable movements by means of the direct or indirect contact with the inside of the cortical bone in the collum.

10 Brief description of the appended drawings

~~Fig 1 is a section of a femur with the fixture mounted,~~
the femur but not the fixture being sectioned,

15 Fig 2 illustrates a combined reamer and cutter for shaping the recess in the collum for the fixture,

Fig 3 illustrates the shape of the recess in the collum, and

20 Figs 4 and 5 show a section of the collum with the recess with and without the fixture.

25 Detailed description of a preferred embodiment of the invention

As can be seen in figs 1 and 5, the fixture comprises two main parts, an elongate, cylindrical first part 1 and a second plug-like, generally cylindrical part 2. The first part 1 is provided with relatively large and widely spaced threads 3 on a major or main part of its outside, the remainder 4 of its outside being smooth and slightly conical. On the end surface of the slightly conical end of the first part 1 a narrow, threaded part 17 is located which is coaxial with the first part 1.

The first part 1 is to fit in a channel or hole 5 drilled longitudinally and centrally through the collum 6. The head 7 of the first part 1 is to be located on the outside of the femur and may, but need not (cf Fig 5), be locked against rotation by means of an elongate plate 8 having a recess 9 with a shape complementary to the shape of the head 7 of the first part 1. The elongate plate is attached to the femoral shaft by means of screws 10. The head 7 of the first part may, but again need not, also be covered by means of a nut 11 having threads being complementary to the threads 3.

A longitudinal bore being provided with threads is provided in the end surface or head 7 of the first part 1. This bore is complementary to a threaded tap on a guide rod having the same diameter as the first part.

The second part 2 is in the shape of a cylindrical plug. One part 12 of the plug is to be inserted into a recess 14 cut in the collum, cylindrically and co-axially with the channel or hole 5. The outside of the part 12 of the plug is provided with threads 15 similar to the threads 3 on the first part 1. The plug 12 is delimited by a circumferential flange 16 limiting the insertion of the plug 12 into the cavity or recess 14. The plug 12 further is provided with a central hole 26 having two parts, an inner, threaded part 27 having an inner diameter corresponding to the outer diameter of the threaded narrow part 17 of the first part 1 and an outer, unthreaded part 20 which is slightly conically flaring in a way corresponding to the unthreaded part 4 of the first part 1 of the fixture.

The threaded parts 17, 27 as well as the threaded parts 1, 12 may be right-handed or left-handed depending on which side of the body they are to be mounted.

The threads on the first and second parts preferably are self-tapping. This can for instance be achieved in that the distal ends of the first and the second part are provided with sharpened recesses 21, 22 in a manner similar to self-tapping screws. The recesses 22 on the second part 2 extend all the way to the end surface of the second part. The recesses 21 on the first part 1 do however not extend all the way to the end surface or head 7, since this part of the first part 1 normally is to be located in the soft tissue and for this reason should not have any sharp edges. This is especially important if no covering nut 11 is used.

The first part 1 is made in several versions with different lengths and the second part 2 is made in several versions with different diameters of the plug part 12.

The plug finally is provided with a conical projection or attachment cone 13 for carrying the ball or caput 18 which is provided with a complementary conical hole 19.

The first and the second part of the fixture preferably are made of c.p. (commercially pure) titanium and may be subjected to a suitable surface treatment. The elongate plate 8 preferably is made of a suitable titanium alloy, whereas its attachment screws 10 preferably should be made of c.p. titanium and for instance have a diameter of 4.5 mm. The attachment cone can be made of a titanium alloy or of c.p. titanium and should be treated in a suitable way to minimize the risk for fretting corrosion. The caput preferably should be made of a ceramic material, also in order to minimize the risk for fretting corrosion.

The socket or acetabulum is not part of the present invention and may be of any commercially available kind

which is suitable.

The operation for implanting the hip joint prosthesis is preferably performed in a one-stage operation.

5

Any differences in the length of the legs are measured. An estimate of the narrowest diameter of the collum is made in order to obtain an idea of the size of the implant to be used.

10

With great care not to disturb the blood circulation, the hip is exposed through an anteriolateral approach. The hip joint is then dislocated. A guide instrument for a cutting tool is attached. The caput is then cut off and removed.

15

The narrowest part of the collum is measured directly in order to obtain further information regarding the size of the implant.

20

A drill is then oriented by means of the guide instrument in such a way relative to the surface of the section that the drill is aligned with the longitudinal extent of the collum and is located at the center of a circle which touches the inside of the cortical bone in the section in at least three points. The diameter of this circle is determined. A hole 5 having a diameter corresponding to the diameter of the first part 1 is then drilled through the collum from the surface of the section, cf fig 2.

25

30

The cylindrical recess or hole 14 is then cut longitudinally in the collum from the direction of the caput by means of a rotary cutting (milling) tool 23. The cutting tool is provided in several sizes, each size corresponding to one size of a second part.

35

The cutting tool comprises a cylindrical, elongate guide

part 24 which has a diameter corresponding to the diameter of the hole 5. The tool further comprises a reamer 25 which is coaxial with the guide part 24, the diameter thereof being chosen to correspond to the diameter of the above circle touching the cortical bone. The diameter and the length of the reamer also corresponds to one of several standard sizes of the second part 2. The tool 23 finally also comprises a surface cutter 26.

10

The guide 24 is inserted into the hole 5 until the reamer 25 engages the surface of the section. The cylindrical recess 14 is then cut by means of the reamer until the surface cutter 26 engages and machines the surface of the section. The object of this machining is to ensure that the surface of the section is smooth and is oriented orthogonally relative to the longitudinal axis of the hole 5. This is important since the longitudinal direction of the collum not necessarily is orthogonal relative to the surface of the section. The resulting cavity 5, 14 can be seen in fig 3.

15

20

A first part having a suitable length and a second part having a suitable diameter are then chosen and attached to each other by means of the threaded part 17 on the first part 1 and the threaded hole 27 in the second part. The respective conically shaped parts 4, 20 on the first and the second part will ensure a secure and tight connection between the two parts.

25

30

The above-mentioned guide rod or extension, which has a diameter corresponding to the diameter of the hole 5, is then mounted on the free end of the first part 1 by means of the threaded bore therein. The guide rod is then inserted into the hole 5 until the threads on the first or the second part engage the bone tissue in the collum. The fixture is then screwed into the hole 5 and the

35

recess 14 whilst being kept aligned by said guide, threads simultaneously being cut into the bone tissue on the inside of the hole 5 and the recess 14 in the collum until the flange or collar 16 abuts the cortical bone on the cut end surface of the collum. Due to the machining by means of the cutter 26, the flange or collar 16 will fit snugly against the surface of the section. The guide rod is then removed.

Finally a ball or caput 18 is mounted on the attachment cone 13 and a reduction or repositioning of the joint is made in order to test the stability of the joint and the length of the leg. The length of the leg is corrected by using caputs having differently sized conical holes 19. The operation is then completed.

After the operation the hip joint soon can be subjected to loads to a limited extent since the design of the fixture will ensure that the fixture is stable to an extent which is sufficient to allow osseointegration.

Possible modifications of the invention.

The invention of course can be varied in many ways within the scope of the appended claims.

As mentioned above, the fixture can be made in one, integral part, which may be advantageous in some applications even if it might greatly increase the number of different types to be kept in stock.

It is also possible to allow the first part of the fixture to end in the cancellous bone tissue before it reaches the cortical bone tissue on the outside of the femur, which may eliminate the necessity of disturbing the cortical bone and the soft tissue on the outer side of the femur.

It may not always be necessary to achieve the three-point contact between fixture and cortical bone in the collum femoris discussed above. This may be of particular importance if the collum femoris has such a shape that it more or less is impossible to obtain said three-point contact. In some cases it may also be more important to center or orient and size the fixture in such a way that a maximal bone contact is obtained. In one extreme it might also be conceivable to design or choose the first and second part of the fixture to have the same diameter. However, if the lateral femoral cortex is to be penetrated, the diameter of the first part should be kept at a minimum.

To express the advantages of the device somewhat differently, the hip joint prosthesis as set forth in the appended claims provides a cylindrical, longitudinal fixture which may be centered in the collum femoris. This allows a dimensioning of the device permitting a maximal bone contact whilst minimizing the risk of perforating the cortical bone in the collum femoris. The fixture permits the penetration of the lateral femoral cortex by means of a threaded extension thereof which may have a smaller diameter than the rest of the fixture may have a flange or abutment collar which may be made to fit exactly against the cut end of the collum femoris by means of a guided bone cutting tool. The fixture can be positioned by means of a drill guide permitting the above centering in conjunction with a centering guide. This, in conjunction with a self-tapping design of the fixture, preferably in pure or almost pure titanium, allows the achievement of an optimal bone contact.

CLAIMS:

1. A hip joint prosthesis for permanent anchoring in the human hip joint comprising an attachment part for a ball unit (18) being designed to be anchored in the neck of a human femur (collum femoris), said attachment part, which is intended to be inserted into a channel (5, 14) extending through the femoral collum, being provided with parts for carrying a ball or caput (18) intended to be attached to the collum after removal of the head of the femur, characterized in that the attachment part also comprises a fixture part comprising two main parts, a first part (1) which is to extend through a bore-hole (5) from the collum femoris towards the outer side of the femur and a second part (2) intended to fit into a cylindrical cavity (14) cut into the cancellous bone of the collum.
2. Hip joint prosthesis according to claim 1, characterized in that said first part (1) which is available in different lengths, is to extend through a longitudinal hole (5) in the collum femoris to the outer side of the femur.
3. Hip joint prosthesis according to any one of claims 1 or 2, characterized in that said second part (2), which is available in different sizes in respect of the diameter, is plug-like and is intended to fit into a cylindrical countersunk cavity (14) cut into the cancellous bone of the collum.
4. Hip joint prosthesis according to claim 3, characterized in that said cylindrical cavity (14) extends to the cortical bone in at least three locations, the size of said second part (2) being chosen such that the fixture abuts the cortical bone of the collum in at least said three locations.


5 5. Hip joint prosthesis according to any one of the preceding claims, c h a r a c t e r i z e d in that said first part (1) and said second part (2) are provided with external threads (3, 15) which preferably are self-tapping.

10 6. Hip joint prosthesis according to claim 6, c h a r a c t e r i z e d in that said threads are right-handed or left-handed depending on whether the prosthesis is to be implanted in the left or the right hip.

15 ~~7. Hip joint prosthesis according to any one of the~~ preceding claims, c h a r a c t e r i z e d in that said second part (2) is provided with a radially oriented, circumferential flange (16) adapted to engage the cut cross-sectional end face of the collum when the prosthesis is mounted in the collum.

20 8. Hip joint prosthesis according to any one of the preceding claims, c h a r a c t e r i z e d in that said first part (1) and said second part (2) are separate parts which are provided with provided with means (17, 27; 4, 20) for firmly and tightly interconnecting said parts.

25 9. Hip joint prosthesis according to any one of claims 1 - 6, c h a r a c t e r i z e d in that said first part (1) and said second part (2) are joined to form, or made as, one integral part.



2/3




FIG 3




FIG 2

3
3




FIG 5

FIG 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 93/00169

A. CLASSIFICATION OF SUBJECT MATTER

IPC5: A61F 2/32 // A61F 2/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC5: A61B, A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE, C2, 2724234 (HUGGLER, ARNOLD), 2 January 1986 (02.01.86), figure 1 --	1-4,7-8
X	DE, B2, 2854334 (ERLER, FRITZ), 23 April 1981 (23.04.81), column 5, line 56 - column 6, line 6, figures 1,4 --	1-5,9
X	DE, A1, 3420035 (SCHEUNEMANN, RÜDIGER), 5 December 1985 (05.12.85), figure 2 --	1-5,7,9

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "B" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

2 June 1993

Date of mailing of the international search report

07 -06- 1993

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Leif Brander
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 93/00169

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR, A1, 2438470 (RAMBERT ANDRE ET AL), 9 May 1980 (09.05.80) -----	1-5,7-8

INTERNATIONAL SEARCH REPORT
Information on patent family members

30/04/93

International application No.
PCT/SE 93/00169

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-C2- 2724234	02/01/86	CH-A- 602091 FR-A,B- 2353275 GB-A- 1579769 JP-A- 52148995 US-A- 4129903	31/07/78 30/12/77 26/11/80 10/12/77 19/12/78
DE-B2- 2854334	23/04/81	NONE	
DE-A1- 3420035	05/12/85	EP-A- 0183744	11/06/86
FR-A1- 2438470	09/05/80	GB-A- 2033755	29/05/80

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)